

CERTIFICATE OF PRODUCT CONFORMITY

Dubai Central Laboratory Department (DCLD) of Dubai Municipality
hereby attests that the product(s)

Rigid Cellular Polystyrene Thermal Insulation

(Details as per the attached Scope of Certification)

manufactured by:

EMIRATES EXTRUDED POLYSTYRENE

Plot No. 598-119, Dubai Investment Park, Dubai, UAE

have been assessed in accordance with DCLD Document Ref. No. DM-DCLD-RD-DP21-2001 (IC) "General Rules for DM third party product certification system through factory assessment" and the relevant Specific Rules, and were found in conformity with the standard specification:

ASTM C 578:18

Accordingly, DCLD hereby authorizes the above manufacturer
to affix the DCL Product Conformity Mark on the above-mentioned product(s).



ARIF AL MARZOOQI

Certification and Quality Control of Products Section Manager
Dubai Central Laboratory Department-Dubai Municipality



Certificate No: CL08020044
Valid Until: 26/03/2024



Current Issue Date: 27/03/2023
Original Issue Date: 27/03/2008



The attached Scope of Certification bearing the same Certificate Number forms an integral part of this Certificate.
This Certificate is an electronic document subject to the Terms and Conditions of the Product Certification System and shall not be reproduced except in full.



DUBAI CENTRAL LABORATORY DEPARTMENT
DCLD-CQPS PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL08020044

Certificate Issued To:	EMIRATES EXTRUDED POLYSTYRENE LLC Plot 598-119, Dubai Investment Park, Dubai, UAE
Applicable Standard Specification:	ASTM C 578: 2018 – Standard Specification for Cellular Rigid Polystyrene Thermal Insulation
Applicable Specific Rules:	DM-DCLD-RD-DP21-2106 (IC) - “Specific rules for certification of rigid cellular polystyrene thermal insulation as per ASTM C 578-18 through factory assessment”.

S/N	PRODUCT DESCRIPTION	BRAND NAME	PRODUCT DETAILS
1	Rigid Cellular Extruded Polystyrene Thermal Insulation Board (See Note 4) CFC Free (see Note 3)	E-FOAM	Size: 1250 x 600 mm Thickness: 25-100 mm ASTM Type VI (as per Table 1)
			Size: 1250 x 600 mm Thickness: 50-100 mm ASTM Type VII (as per Table 1)

Note 1: This document forms an integral part of the Certificate of Product Conformity bearing the same certificate number.

Note 2: The above products shall bear the DCLD Conformity Mark (applied on each product or on the packaging).

Note 3: CFC Free as per declaration from the company, in accordance with the 2020 Al Sa'fat Dubai Green Building System.

Note 4: The product is an insulation for flat roofs covered by concrete used in conjunction with external roof waterproofing systems.

TABLE 1 (EXTRUDED)



DUBAI CENTRAL LABORATORY DEPARTMENT
DCLD-CQPS PRODUCT CONFORMITY CERTIFICATION SCHEME

SCOPE OF CERTIFICATION
FOR CERTIFICATE NO. CL08020044

**PHYSICAL PROPERTY REQUIREMENTS OF RIGID CELLULAR
POLYSTYRENE THERMAL INSULATION**

SN	PROPERTIES	TYPE XII	TYPE X	TYPE XIII	TYPE IV	TYPE VI	TYPE VII	TYPE V
1	COMPRESSIVE RESISTANCE @ yield or 10% deformation, which occurs first, min kPa	104	104	138	173	276	414	690
2	THERMAL RESISTANCE of 25.4 mm thickness, @ mean temp. 35°C and 60% RH min, K-m ² /W	0.77	0.84	0.65	0.84	0.84	0.84	0.84
3	THERMAL CONDUCTIVITY , max, W/m·K @ 35°C and 60% RH	0.0330	0.0303	0.0392	0.0303	0.0303	0.0303	0.0303
4	FLEXURAL STRENGTH , min, kPa	276	276	310	345	414	517	690
5	WATER VAPOR PERMEANCE of 25.4 mm thickness, max, perm	1.5	1.5	1.5	1.5	1.1	1.1	1.1
6	WATER ABSORPTION by total immersion, max volume %	0.30	0.30	1.0	0.30	0.30	0.30	0.30
7	DIMENSIONAL STABILITY (change in dimension), max, %	2.0	2.0	2.0	2.0	2.0	2.0	2.0
8	OXYGEN INDEX , min, volume %	24	24	24	24	24	24	24
9	DENSITY , min, kg/m ³	19	21	26	23	29	35	48

NOTE: The above specification values are extracted from Table 1 of ASTM C578: 2018

Original Issue Date: 27 March 2008
Current Issue Date: 27 March 2023
Valid Until: 26 March 2024

ARIF HUSAIN AL MARZOOQI

MANAGER

CERTIFICATION AND QUALITY CONTROL OF PRODUCTS SECTION